



TY350S WH

DuPont™ Tyvek®



Line Drawing



Serged Seam

FEATURES AND BENEFITS

Tyvek® garments are composed of flash spun high density polyethylene which creates a unique, nonwoven material available only from DuPont. Tyvek® provides an ideal balance of protection, durability and comfort of any limited use fabric technology. Tyvek® fabric offers an inherent barrier against particles (down to 1.0 micron in size). Protection is built into the fabric itself; there are no films or laminates to abrade or wear away. Tyvek® fabric's durability advantage over microporous film fabrics delivers consistently better barrier, even after wear and abrasion. Applications include: lead and asbestos abatement/remediation, general maintenance/operations, spray painting, general clean-up.

- Pants with open ankle and elastic at waist for easy donning and removal
- Suitable for applications that do not require the full body coverage of a coverall
- Typically worn with TY303S WH shirt.

[See all Product Literature](#)

Product Description

DuPont™ Tyvek® Pants. Open Ankles. Elastic Waist. Elastic Waist. Serged Seams. White.

**Full Part Number: TY350SWHxx0050yy** (xx=size; yy=option code)

**Fabric:** Tyvek®

**Style:** Pants

**Seam:** Serged

**Color:** White

**Sizes:** SM, MD, LG, XL, 2X, 3X, 4X, 5X, 6X, 7X

**Case Count:** 50 per case

**Option Codes:** 00, PI

[Product Terms of Use and Warranty](#) (PDF)

PRODUCT DETAILS

Available Options

Option Code	Description	Available Sizes	Part Number
00	Standard	SM, MD, LG, XL, 2X, 3X, 4X, 5X, 6X, 7X	TY350SWHxx005000
	(s/p) Individually packaged. For select Tyvek® styles only (TY120S WH, TY122S WH, TY125S WH and TY127S WH)		
PI	- individually packaged for PPE vending machines	SM, MD, LG, XL, 2X, 3X	TY350SWHxx0050PI

Finished Dimensions


Typical Finished Dimensions

Size	Inseam	Waist Opening
SM	27	22
MD	27 1/2	23 1/2
LG	28	24 3/4
XL	28 3/4	25 1/2
2X	29 1/2	26 1/2
3X	30	27 1/2
4X	30 3/4	28 1/4
5X	31 1/4	29
6X	32	29 3/4

7X

32 1/4

30 1/2



### Specifications

1. The garment shall be constructed of DuPont™ Tyvek® – a patented flash-spun polyethylene fabric.
2. The garment shall be white in color.
3. The garment shall be a pants design.
4. The garment shall have serged seams.
5. The garment shall have an elastic waist.
6. The garment shall have open ankles.

### Additional Equipment Needed

- Wear other appropriate PPE such as, but not limited to, respiratory, eye, head, hand, and foot protection based on the hazard assessment.
- This garment only provides partial body coverage. It may be worn in combination with other chemical resistant PPE as required based on the hazard assessment.

## FABRIC DATA

### Physical Properties - Typical Values

#### Tyvek® - Fabric Data

Property	Test Method	Result
Thickness	ASTM D1777	5.7 mils
Basis Weight	ASTM D3776	1.2 oz/yd <sup>2</sup>
Burst Strength - Mullen	ASTM D774	48 psi
Tear Resistance - Trap Tear (MD)	ASTM D5733	5 lb <sup>f</sup>
Tear Resistance - Trap Tear (CD)	ASTM D5733	7 lb <sup>f</sup>
Breaking Strength - Grab (MD)	ASTM D5034	18 lb <sup>f</sup> /in
Breaking Strength - Grab (CD)	ASTM D5034	24 lb <sup>f</sup> /in
Hydrostatic Head	AATCC 127	40 inches H <sub>2</sub> O
Surface Resistivity (25°C / 55% RH)	ASTM D257	< 6.3 x 10 <sup>9</sup> ohms/square
Wearing Apparel Flammability	16 CFR 1610 <sup>(?)</sup>	Class 1

\*Typical values, not specifications.

### Chemical Resistance Data

DuPont Permeation Guide

#### Tyvek® - Fabric Data

Hazard / Chemical Name	CAS Number	Phase	Breakthrough Time
------------------------	------------	-------	-------------------

		(average, normalized to 0.1 ug/cm <sub>2</sub> /min)	
		<b>/ Performance</b>	
Animal Waste (non-hazardous; solid)	unknown	Solid	May be Suitable for Use
Asbestos (all forms)	1332-21-4	Solid	May be Suitable for Use
Beryllium	7440-41-7	Solid	May be Suitable for Use
Biological fluids w/ potentially infectious diseases	unknown	Liquid	May be Suitable for Use
Blood	unknown	Liquid	May be Suitable for Use
Blood w/ potentially infectious diseases	unknown	Liquid	May be Suitable for Use
Bodily fluids	unknown	Liquid	May be Suitable for Use
Bodily fluids w/ potentially infectious diseases	unknown	Liquid	May be Suitable for Use
Crude oil on wildlife	mixture	Liquid	May be Suitable for Use
Dirt (general)	unknown	Solid	May be Suitable for Use
Feces (solid)	unknown	Solid	May be Suitable for Use
Fertilizer (general; solid form)	unknown	Solid	May be Suitable for Use
Fiberglass	unknown	Solid	May be Suitable for Use
Fungicide (general; solid form)	unknown	Solid	May be Suitable for Use
Grease (general)	unknown	Liquid	May be Suitable for Use
Hazardous Particles (larger than 1 micron in size)	unknown	Solid	May be Suitable for Use
Herbicide (general; solid form)	unknown	Solid	May be Suitable for Use
Insecticide (general; solid form)	unknown	Solid	May be Suitable for Use
Lead	7439-92-1	Solid	May be Suitable for Use
Lime	mixture	Solid	May be Suitable for Use
Mold spores	unknown	Solid	May be Suitable for Use
Non-Hazardous Particles (larger than 1 micron in size)	unknown	Solid	May be Suitable for Use
Pesticide (general; solid form)	unknown	Solid	May be Suitable for Use
Radioactive particles	unknown	Solid	May be Suitable for Use
Sewage	unknown	Liquid	May be Suitable for Use
Tar balls	unknown	Solid	May be Suitable for Use

### Special Warnings

- \*Serged and bound seams are degraded by some hazardous liquid chemicals, such as strong acids, and should not be worn when these chemicals are present.
- \*Liquid barrier performance varies based on the amount of liquid that may get on the garment, the length of time the liquid is on the garment, applied pressure and certain physical properties of the liquid. Tyvek®, Tyvek® Dual, ProShield®, ProShield® Basic, ProShield® NexGen®, Tyvek® FC, and ProShield® 3 garments are not appropriate if during use they are getting wet (liquid is dripping or running, or it is wet to the touch) or if spotting is observed on skin or garments worn under the protective garment. Tyvek® Xpert and Tyvek® Plus offer improved liquid barrier, but may not be appropriate if spotting is observed on the skin or garments worn under the protective garment. In applications where a higher liquid barrier is needed, consider Tychem® QC and Tychem® SL garments with taped seams.
- Tyvek® Plus and Tyvek® Xpert fabric have different fabric physical properties and improved chemical resistance properties than standard Tyvek® garments.
- \*CAUTION: This information is based upon technical data that DuPont believes to be reliable. It is subject to revision as additional knowledge and experience are gained. DuPont makes no guarantee of results and assumes no obligation or liability in connection with this information. It is the user's responsibility to determine the nature and level of hazards and the proper personal protective equipment needed. The information set forth herein reflects laboratory performance of fabrics, not complete garments, under controlled conditions. It is intended for information use by persons having technical skill for evaluation under their specific end-use conditions, at their own discretion and risk. Anyone intending to use this information should first verify that the garment selected is suitable for the intended use. In many cases, seams and closures have shorter breakthrough times and higher penetration rates than the fabric. Please contact DuPont for specific data. These garments are intended for limited use and should be disposed of after single use. If fabric becomes torn, abraded or punctured, or if seams or closures fail, or if attached gloves, visors, etc are damaged, end user should discontinue use of garment to avoid potential exposure.