


824

Multi-Purpose PE Tape



Backing: Polyethylene Film

Adhesive: Rubber

Liner: N/A

Colors: Red, White, Yellow

Specifications: N/A

Standard Sizes: 48mm x 55m, 72mm x 55m

Applications

- Stucco & plaster masking
- General purpose outdoor masking

- Bunding, wrapping, and repairs
- General purpose abatement applications such as hanging and patching PE sheeting, securing waste disposal bags, and more.

Features Benefits

- Polyethylene Film Backing
- Natural rubber based adhesive
- Low VOC Content

LEADERSHIP BY DESIGN

- Conformable and flexible
- Excellent durability & solvent resistance
- Withstands outdoor exposure and moisture
- High tack for a secure bond
- Repositionable & clean removal no residue
- Can contribute toward satisfying EQ Credit 4.1
 (Low Emitting Materials) under LEED®

Physical Properties

	Standard UOM	Metric UOM	Test Method
Total Thickness	7 mils	177.8	ASTM D-1000
Adhesion to Steel	45 oz/in	4.93 N/cm	PSTC-101
Tensile Strength	20 lb/in	35.03 N/cm	ASTM D-1000
Operating Temperature	40-200°F	4-93°C	
VOC Content	<2 g/L		
Elongation	75%		

Recommended Storage Conditions: 40-60% Humidity, 60°F-80°F Standard Shelf Life (at 25C): 24 months from date of manufacture.

The information presented herein was prepared at BERRY PLASTICS CORPORATION (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry Plastics' knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws, and regulations. The data are typical values submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal responsibility.

Niiverheidsstraat 10