



VIPER PRESTIGE

Water-Based Impregnating Sealer

Water-based sealer slows down the penetration of liquid and especially oils, yet water vapor permeable to allow moisture in the substrate to evaporate.

	Concrete, Grout	Granite	Limestone, Travertine	Marble	Flagstone, Slate
Water Repellency	**	***	***	***	**
Oil Repellency	***	***	***	***	***
	*** Excellent	** Good	* Suitable		



HYDRO-FORCE®

One U.S. Gallons (3.79 Litres)

RTU ph - 10.0

FOR PROFESSIONAL USE ONLY.
VOC content for product is: 0 g/L

- Fluoro-chemical technology provides maximum protection against spots and spills
- Protects without affecting slip resistance
- Preserves the natural look of stone and can be applied to interior surfaces
- Ideal water based sealer for prestigious stones like marble, granite, limestone, and travertine.

DIRECTIONS FOR USE: DIRECTIONS FOR USE:

Before Application
SHAKE THOROUGHLY BEFORE EACH USE! Test for suitability in an inconspicuous area, especially for polished marble and extremely porous surfaces. Ensure that the area is well-ventilated during application and until the surface is dry. Keep children and pets out of the area until foot traffic resumes. Sealer may be applied to damp surfaces one hour after standing water has been removed. Surface temperature should be between 50°F and 80°F. Mask any surfaces not intended to be treated.

Cleaning Is Necessary

Surface must be cleaned and thoroughly rinsed to neutralize pH and remove residues. Dry stone enables the best penetration into the surface of stone. Make sure that there are no puddles in grout lines and use air movers to speed the drying of the stone and grout lines before application.

Dilution Instructions

Do not dilute. The product is ready to use. Coverage should be between 300 and 1200 sq. ft. per gallon depending on the porosity of the surfaces and the coverage required.

Application Methods

Stone Application
For entire floor application, spray on sealer using sprayer

maintaining 35 to 50 psi with an 2004 TeeJet nozzle. Spread evenly with a brush with synthetic fibers. An alternative and sometimes preferred application method is to liberally apply an even coat using a paint pad, roller or brush. Allow sealer to penetrate the surface for 15–30 minutes. During this time, distribute sealer over entire area to ensure even penetration. Stone density will vary over the same stone so more may be necessary in some areas and less in other areas. Remove excess sealer by wiping entire surface thoroughly with clean, dry towels. A second coat may be necessary after 1 hour. Place drop of water on newly sealed stone and see if it absorbs into grout or stone. If it does absorb readily, then a second coat is necessary.

Post Application Precautions

Floor is typically walkable in 3 to 4 hours, ready for use after 8 to 12 hours, and completely cured in 24 hours. After 6 to 18 months, reapplication may be necessary, depending upon the traffic level, maintenance procedures and the type of surface sealed.

INGREDIENT DISCLOSURE:

Water, Fluorinated Acrylic Alkylamino Copolymer, Butoxydiglycol, Benzisothiazolinone.

IMPORTANT NOTICE TO PURCHASER: Seller's and manufacturer's liability for any and all losses or damages resulting from any cause whatsoever shall in no event exceed the purchase price of this product, with respect to which losses or damages are claimed. Before using, the user shall determine the suitability of this product for its intended use, and user assumes all risk and liability whatsoever in connection therewith. Go to www.hydroforce.com/sds for additional safety, regulatory and liability information.

CAUTION

Keep out of reach of children.

HAZARD STATEMENTS:

May be harmful if swallowed. Causes eye irritation.

PRECAUTIONARY STATEMENTS:

Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Wear protective gloves/protective clothing/eye protection/face protection. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF ON SKIN: Wash with plenty of soap and water. Get medical advice/attention if you feel unwell. IF SKIN irritation occurs: Get medical advice/attention.

No GHS Pictogram

PRECAUCIÓN

Mantener fuera del alcance de los niños.

INDICACIONES DE PELIGRO:

Mi ser perjudicial si se ingiere. Provoca irritación ocular.

CONSEJOS DE PRUDENCIA:

No respirar el polvo/el humo/el gas/la niebla/los vapores/ el aerosol. Evitar el contacto con los ojos, la piel o la ropa. Usar guantes/ropa de protección/equipo de protección para los ojos/la cara. EN CASO DE CONTACTO CON LOS OJOS: Aclarar cuidadosamente con agua durante varios minutos. Quitar las lentes de contacto, si lleva y resulta fácil. Seguir aclarando. EN CASO DE CONTACTO CON LA PIEL: Lavar con agua y jabón abundantes. Consultar a un médico en caso de malestar. En caso de irritación cutánea: consultar a un médico.

No hay pictograma GHS

PRUDENCE

Tenir hors de portée des enfants.

MENTIONS DE DANGER:

Mon être nocif en cas d'ingestion. Provoque une irritation des yeux.

CONSEILS DE PRUDENCE:

Ne pas respirer les poussières/fumées/gaz/brouillards/vapeurs/aérosols. Éviter tout contact avec les yeux, la peau ou les vêtements. Porter des gants de protection/des vêtements de protection/ un équipement de protection des yeux/du visage. EN CAS DE CONTACT AVEC LES YEUX: rincer avec précaution à l'eau pendant plusieurs minutes. Enlever les lentilles de contact si la victime en porte et si elles peuvent être facilement enlevées. Continuer à rincer. EN CAS DE CONTACT AVEC LA PEAU: laver abondamment à l'eau et au savon. Consulter un médecin en cas de malaise. En cas d'irritation cutanée: Consulter un médecin.

Pas de pictogramme GHS

Made in the USA with globally sourced materials.
Hecho en los USA con materiales de origen mundial.
Fabriqué aux USA avec des matériaux provenant du monde entier.

Warning: For California residents only/Pour les résidents de la Californie seulement. **WARNING:** This product can expose you to chemicals including Acetaldehyde and 1,4-Dioxane, which are known to the State of California to cause cancer, and Ethylene Glycol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

See Safety Data Sheet (SDS):
www.hydroforce.com/sds
for additional safety and regulatory information.

Another fine product from Hydro-Force Manufacturing
4282 South 590 West, Salt Lake City, UT 84123
1-3680 Odyssey Drive, Mississauga, ON L5M 0Y9
www.hydroforce.com | 800-658-5314

