## TUFT GUARD II

## **Fluorochemical Carpet Protector**





Provides the absolute latest and most advanced technology in fluorochemical and acid dye resistors (dye-blockers) for maximum stain prevention and enhanced soil resistance. Best choice for nylon and wool carpets.



- 3.89 L (1 US gal.) Part number 2628-0204
- 18.93 L (5.28 US gal.) Part number 2696-4462



Directions: Dilute by mixing 1 part concentrate protector with 4 parts water.

Application: Apply to freshly cleaned carpet using an electric or battery powered sprayer maintaining 35 to 50 psi with an 8004 or 8005 TeeJet nozzle. Apply evenly over entire carpet surface. For use with Hydro-Force sprayer, remove metering tip to achieve 1 to 4 dilution.

Coverage: 240 to 480 sq ft per diluted gallon for damp or dry carpet. Coverage depends on carpet pile density; i.e. heavy pile residential requires 1 RTU gallon per 240 sq ft. low pile commercial requires 1 RTU gallon per 480 sq ft.

If accidental freezing occurs, allow to thaw at room temperarture, then shake vigorously.

Keep this product out of reach of children. Read the Material Safety Data Sheet and Product Label before using. Take the necessary precautions dictated by the label to ensure that your health and that of your customers' is protected.

FOR SDS VISIT /POUR CONSULTER LES FDS VISITEZ LE: www.esteam.com

