

TRUCKMOUNT DESCALER NEUTRALIZER



Truckmount Descaler and Neutralizer is a 2-part descaling system that effectively descalses the toughest jobs, while also being safer for the technician and environment. Step 1 removes scale and deposits from your truckmount so it can run more efficiently, and Step 2 neutralizes the acidic wastewater so you are compliant with local wastewater regulations. This helps our water treatment plants operate more effectively, and minimizes your liability and risk of paying steep fines.

- REMOVES THE TOUGHEST SCALE – our Truckmount Descaler is a perfect blend of acidity and surfactancy to allow the descaler to penetrate deeply into built-up scale and remove even the toughest buildup.
- LOW COST - concentrated powder means you use less and save money.
- EQUIPMENT SAFE - special additives protect metals from corrosion.
- SAFER FOR THE OPERATOR – powdered descalers are safer than liquid descalers as they reduce opportunities for splash injury and make handling easier.
- SAFER FOR THE ENVIRONMENT – 2-step process effectively descalses equipment, but also neutralizes wastewater so it's compliant with local wastewater regulations.

Available in:

2 lbs (0.91 kgs) - Part # 2658-3450 Step 1

3.79 L (1 U.S. Gallon) - Part # 2698-4500 Step 2

DIRECTIONS:

1. Disconnect truckmount water inlet and solution outlet hoses.
2. Drain enough water from the truckmount water box to allow enough space to empty the entire container of Truckmount Descaler Step 1 into the water box. There must be enough liquid to allow the Step 1 powder to mix and become liquid, and for a gallon of Step 2 to be added last as a neutralizer. An appropriate amount for most truckmounts is a half-full water box.
3. Run truckmount to warm water (not hot).



4. Slowly sprinkle 2 pounds (entire bottle) of Truckmount Descaler Step 1 into waterbox to dissolve while truckmount is running.
5. Let truckmount run for 15 to 30 minutes (depending on severity of scale) to release scale from metal parts.
6. Add Truckmount Descaler Neutralizer Step 2 while truckmount is running for 2 minutes to neutralize acid.
7. Flush with clear water for five minutes after starting release of neutralized wastewater.

**Keep this product out of reach of children. Read the Safety Data Sheet and Product Label before using.
Take the necessary precautions dictated by the label to ensure that your health and that of your customers' is protected.**

FOR SDS VISIT /POUR CONSULTER LES FDS VISITEZ LE: www.esteem.com

