

Chemsafe® Brands

Product Specifications

Item A58560 (5 gal /pail)

Item A58561 (55 gal./drum)



Product Description:

Chemsafe 100C Low Odor Mastic/Adhesive Remover is a specifically formulated product developed by Chemsafe Brands for use in the quick and efficient removal of asphaltic floor tile mastic. Chemsafe 100C is a CARB / OTC Compliant version of our Chemsafe 100. This fast-acting emulsifiable solvent quickly dissolves floor tile mastic and is equally efficient in removing spray adhesive and natural pastes and glues on tough asbestos abatement jobs. The high penetrant content quickly softens the mastic (or adhesive) within minutes of complete saturation, and in many instances, can be completely liquefied using a squeegee or push broom. In addition, the special emulsifiers found in Chemsafe 100C assist in its high rinseability.

The composition of the low-odor organic hydrocarbons found in Chemsafe 100C is ideally suited for use in areas where chemical smells are a cause for concern. This product offers the fastest, most economical way of undertaking any type of floor tile adhesive removal project.

- Low Odor / Fast Acting
- $\geq 141^{\circ}\text{F}$ Flash Point
- Economical
- Emulsifiable
- CARB / OTC Compliant

Directions for Use:

Saturate mastic to be removed manually or with a garden sprayer. Allow time for remover to penetrate and soften mastic. Dislodge with stiff broom and/or squeegee, repeat if necessary. Thoroughly rinse, wash, and/or clean treated surface upon completion of job. Surface must be completely rinsed clean and allowed to dry before any replacement materials can be installed. Dispose of in accordance with federal, state and local regulations.

Product Data:

General ID	Hydrocarbon Mixture	Vapor Pressure (mm hg)	CARB / OTC Compliant
Odor	Very Light Solvent	Clean Up	Water & Detergent
Color	Blue Liquid	Reactivity	Stable
Flash Point	$\geq 141^{\circ}\text{F}$	Application	Manual or Airless
Coverage	75-100 sq. ft./gal	Shelf Life	1 Year
Vapor Density (air=1)	>1	Shipping Class	55
Solubility in Water	Emulsifies in water	Shipping Weight	5 gal. = 37 lbs. 55 gal. = 415 lbs.
Specific Gravity (water=1)	.8277	DOT Shipping Name	Combustible Liquid NOS
Percent Volatile	90-99	DOT Hazard Class	3, PG III, NA1993
Evaporation Rate (butyl acetate=1)	<1		
Boiling Range	$>300^{\circ}\text{F}$		

If shipped under 119 gallons per container, product has been certified by DOT as being NON-REGULATED.

DISTRIBUTED EXCLUSIVELY BY ARAMSCO, INC. :

PHILADELPHIA (800) 767-6933	CHICAGO (800) 767 9981	HOUSTON (800) 767-8392	DALLAS (800) 767-5744	PHOENIX (800) 767-9372	NEW ORLEANS (866) 767-9180	CORPORATE-NEW JERSEY (800)767-6933	
BOSTON (800) 767-1767	HARTFORD (800) 767-7731	NEW YORK CITY (888) 767-4359	SAN JUAN (787) 880-0335	LOS ANGELES (800) 767-4620	TAMPA (800) 767-1225	DURHAM (888) 941-6368	ROCHESTER-NY (800) 767-4101