

Print Date: 01-09-2017

FOSTER 40-50 (FD4050)  
820379PM

## SAFETY DATA SHEET

REVISION DATE: 05-01-2015

SUPERSEDES: 02-06-2015

### SECTION 1: IDENTIFICATION OF THE PRODUCT AND SUPPLIER

#### PRODUCT INFORMATION

**PRODUCT:** FOSTER 40-50 (FD4050)  
**PRODUCT DESCRIPTION:** Coating  
**INTENDED USE:** Coating  
**PRODUCT IDENTIFIER:** 820379PM

#### COMPANY INFORMATION

H.B. Fuller Construction Products Inc.  
 1105 S. Frontenac Street  
 Aurora, IL 60504  
 Phone: 1-800-552-6225

Medical Emergency Phone Number (24 Hours): 1-888-853-1758  
 Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

### SECTION 2: HAZARDS IDENTIFICATION

#### GHS Hazard Symbols:



**GHS Signal Word:** Danger  
**GHS Classification:** Skin Sensitisation Category 1; Germ Cell Mutagenicity Category 1B; Hazardous to the aquatic environment - Acute Category 2; Hazardous to the aquatic environment - Chronic Category 2  
**GHS Hazard Phrases:** May cause an allergic skin reaction.; May cause genetic defects.; Toxic to aquatic life.; Toxic to aquatic life with long lasting effects.  
**GHS Precautions:**  
**Safety Precautions:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapours/spray. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.  
**First Aid Measures:** IF ON SKIN: Wash with plenty of soap and water. IF exposed or concerned: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. Collect spillage.  
**Storage:** Store locked up.  
**Disposal:** Dispose of contents/container in accordance with local/regional/national/international regulation for hazardous wastes.

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS #	PERCENT	Classification	Note
Barium compound	13701-59-2	5 - 10	Acute Tox. 4; H332 Acute Tox. 4; H302	* (see below)
Titanium dioxide	13463-67-7	1 - 5	Carc. 2; H351	* (see below)

**SAFETY DATA SHEET**

Zinc oxide	1314-13-2	1 - 5	Aquatic Acute 1; H400 Aquatic Chronic 1; H410
Iodo-2-propynyl butylcarbamate	55406-53-6	0.1 - 1	Aquatic Acute 1; H400 Acute Tox. 4; H332 Acute Tox. 4; H302 Eye Dam. 1; H318 Skin Sens. 1; H317 STOT SE 3; H335

\*This product contains one or more materials that may be hazardous when present as an airborne dust. During normal handling of the product, the material is encapsulated within the product and will not present an exposure risk. Once the product has reached its final state and is abraded or disturbed, dusting and exposure may occur.

Unlisted ingredients are not 'hazardous' per the Occupational Safety and Health Administration Hazard Communication Standard (29 CFR 1910.1200) and/or are not found on the Canadian Workplace Hazardous Materials Information System ingredient disclosure list. See Section 8 for exposure limit guidelines.

**SECTION 4: FIRST AID MEASURES**

**IF IN EYES:** Use an eye wash to remove a chemical from your eye regardless of the level of hazard. Flush the affected eye for at least twenty minutes. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Seek medical advice after flushing.

**IF ON SKIN:** Wash with soap and water. Get medical attention if irritation develops or persists.

**IF INHALED:** Remove to fresh air. Call a physician if symptoms persist.

**IF SWALLOWED:** Do not induce vomiting. Seek medical attention if symptoms develop. Provide medical care provider with this MSDS. Induced vomiting may lead to aspiration of the material into the lungs potentially causing chemical pneumonitis that may be fatal.

**SECTION 5: FIRE FIGHTING MEASURES**

**EXTINGUISHING MEDIA:** Use water spray, foam, dry chemical or carbon dioxide.  
**UNUSUAL FIRE AND EXPLOSION HAZARDS:** There is a possibility of pressure buildup in closed containers when heated. Water spray may be used to cool the containers.  
**SPECIAL FIRE FIGHTING INSTRUCTIONS:** Persons exposed to products of combustion should wear self-contained breathing apparatus and full protective equipment.  
**HAZARDOUS COMBUSTION PRODUCTS:** Carbon dioxide, Carbon monoxide Metal fumes Silicon dioxide

**SECTION 6: ACCIDENTAL RELEASE MEASURES**

**SPECIAL PROTECTION:** No adverse health effects expected from the clean-up of spilled material. Follow personal protective equipment recommendations found in Section 8 of this SDS.  
**METHODS FOR CLEAN-UP:** Dike if necessary, contain spill with inert absorbent and transfer to containers for disposal. Keep spilled product out of sewers, watersheds, or water systems.

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

**SECTION 7: HANDLING AND STORAGE**

**Handling:** No special handling instructions due to toxicity.

Print Date: 01-09-2017

FOSTER 40-50 (FD4050)  
820379PM

## SAFETY DATA SHEET

Storage: Store in a cool, dry place. Protect from freezing.  
 Consult the Technical Data Sheet for specific storage instructions.

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### EXPOSURE LIMITS:

Chemical Name	Note	ACGIH EXPOSURE LIMITS	OSHA PEL
Titanium dioxide	* (see below)	10 mg/m <sup>3</sup> TWA	15 mg/m <sup>3</sup> TWA (total dust)
Zinc oxide		2 mg/m <sup>3</sup> TWA (respirable fraction) 10 mg/m <sup>3</sup> STEL (respirable fraction)	5 mg/m <sup>3</sup> TWA (fume); 15 mg/m <sup>3</sup> TWA (total dust); 5 mg/m <sup>3</sup> TWA (respirable fraction)
Amorphous silica	* (see below)	No data available.	20 mppcf TWA; ((80)/(% SiO <sub>2</sub> )) mg/m <sup>3</sup> TWA)

\*This product contains one or more materials that may be hazardous when present as an airborne dust. During normal handling of the product, the material is encapsulated within the product and will not present an exposure risk. Once the product has reached its final state and is abraded or disturbed, dusting and exposure may occur.

#### ENGINEERING CONTROL METHODS:

**VENTILATION:** Use local exhaust ventilation or other engineering controls to minimize exposures.

**EYE PROTECTION:** Wear safety glasses when handling this product.

**SKIN PROTECTION:** Not normally required. Wear chemically resistant gloves to prevent prolonged or repeated contact.

**GLOVES:** Not normally required. Use nitrile gloves if conditions warrant.

**RESPIRATORY PROTECTION:** Respiratory protection may be required to avoid overexposure when handling this product. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms. Respirators should be selected by and used following requirements found in OSHA's respirator standard (29 CFR 1910.134).

### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE:	Liquid
COLOR:	White
ODOR:	Mild Sweet
ODOR THRESHOLD:	Not established
pH:	Not established
FREEZING/MELTING POINT (deg. C):	Not established
BOILING POINT (deg. C):	Not established
FLASH POINT:	Non flammable
EVAPORATION RATE:	Not established
FLAMMABILITY:	Not a flammable solid or gas
UPPER EXPLOSIVE LIMIT (% in air):	Not established
LOWER EXPLOSIVE LIMIT (% in air):	Not established
VAPOR PRESSURE (mm Hg):	Not established
VAPOR DENSITY:	Not established
WEIGHT PER GALLON (lbs.):	11.80
SPECIFIC GRAVITY:	1.360
SOLUBILITY:	Not established

Print Date: 01-09-2017

FOSTER 40-50 (FD4050)  
820379PM

## SAFETY DATA SHEET

OCTANOL/WATER COEFFICIENT:	Not established
AUTOIGNITION TEMPERATURE:	Not established
DECOMPOSITION TEMPERATURE:	Not established
VISCOSITY:	No data available.
SOLIDS (% by weight):	56.0
VOC, weight percent	1.43
VOC, U.S. EPA Method 24, less water and exempt solvents (theoretically determined)	38.1 g/liter of material

### SECTION 10: STABILITY AND REACTIVITY

STABILITY:	Stable under normal conditions.
CHEMICAL INCOMPATIBILITY:	Not established
HAZARDOUS POLYMERIZATION:	Will not occur.
HAZARDOUS DECOMPOSITION PRODUCTS:	Carbon monoxide, carbon dioxide Metal fumes Silicon dioxide

### SECTION 11: TOXICOLOGICAL INFORMATION

#### Component Toxicity / Toxicology Data:

COMPONENT NAME	LD50/LC50
Water	ORAL LD50 RAT > 90 ML/KG
Barium compound	ORAL LD50 RAT 530 MG/KG DERMAL LD50 RABBIT > 2,000.00 MG/KG
Titanium dioxide	ORAL LD50 RAT > 10,000 MG/KG
Zinc oxide	ORAL LD50 RAT > 5,000 MG/KG
Amorphous silica	ORAL LD50 RAT > 5,000 MG/KG INHALATION LC50-1H RAT > 2.20 MG/L DERMAL LD50 RABBIT > 2,000.00 MG/KG
Propylene glycol	ORAL LD50 RAT 20,000 MG/KG DERMAL LD50 RABBIT 20,800.00 MG/KG

**This product is a mixture. Unless noted, the information below is based on components.**

Skin corrosion / irritation: Can cause minor skin irritation, defatting, and dermatitis.

Serious eye damage / irritation :Can cause minor irritation, tearing and reddening.

Respiratory / skin sensitization: No data available.

Germ cell mutagenicity: May cause genetic defects.

Carcinogenicity: Contains a material that may cause cancer.

Reproductive toxicity: No data available.

Specific target organ toxicity-single exposure: No data available.

Respiratory irritation / Narcotic effects: May cause respiratory irritation.

Specific target organ toxicity-repeated exposure: No data available.

Target organs potentially affected by exposure: Lungs

Aspiration hazard: No data available.

Medical Conditions Aggravated by Exposure: Lung disease

Print Date: 01-09-2017

FOSTER 40-50 (FD4050)  
820379PM

## SAFETY DATA SHEET

---

### SECTION 12: ECOLOGICAL INFORMATION

---

OVERVIEW: No ecological information available for this product.  
 MOBILITY: No data available.  
 PERSISTENCE: No data available.  
 BIOACCUMULATION: No data available.

**This product has not been tested for ecological effects. Relevant information for components is listed below:**

Component:	Ecotoxicity values:
Amorphous silica	<b>Acute Toxicity (Fish):</b> 96 Hr LC50 Brachydanio rerio: 5000 mg/L [static] <b>Acute Toxicity (Daphnia):</b> 48 Hr EC50 Ceriodaphnia dubia: 7600 mg/L <b>Acute Toxicity (Algae):</b> 72 Hr EC50 Pseudokirchneriella subcapitata: 440 mg/L
Propylene glycol	<b>Acute Toxicity (Fish):</b> 96 Hr LC50 Oncorhynchus mykiss: 51600 mg/L [static]; 96 Hr LC50 Oncorhynchus mykiss: 41 - 47 mL/L [static]; 96 Hr LC50 Pimephales promelas: 51400 mg/L [static]; 96 Hr LC50 Pimephales promelas: 710 mg/L <b>Acute Toxicity (Daphnia):</b> 24 Hr EC50 Daphnia magna: >10000 mg/L; 48 Hr EC50 Daphnia magna: >1000 mg/L [Static] <b>Acute Toxicity (Algae):</b> 96 Hr EC50 Pseudokirchneriella subcapitata: 19000 mg/L

---

### SECTION 13: DISPOSAL CONSIDERATIONS

---

To the best of our knowledge, this product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. Solidify and dispose of in an approved landfill. Consult state, local or provincial authorities for more restrictive requirements.

---

### SECTION 14: TRANSPORT INFORMATION

---

Consult Bill of Lading for transportation information.

US DOT: NOT REGULATED  
 IATA: NOT REGULATED  
 IMDG: UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (ZINC OXIDE), 9, III, MARINE POLLUTANT

---

### SECTION 15: REGULATORY INFORMATION

---

#### INVENTORY STATUS

U.S. EPA TSCA: This product is in compliance with the Toxic Substances Control Act's Inventory requirements.  
 CANADIAN CEPA DSL: The components of this product are included on the DSL or are exempt from DSL requirements.  
 EUROPEAN REACH: As a result of the introduction of REACH into Europe, this product cannot be imported into Europe unless the REACH requirements are met.  
 AUSTRALIA AICS: This product is in compliance with the Australian Inventory of Chemical Substances requirements.  
 KOREAN TCCL: This product is in compliance with the Korean Existing Chemicals List requirements.  
 CHINA IECSC INVENTORY: This product is in compliance with the Inventory of Existing Chemical Substances in China (IECSC) requirements.

If you need more information about the inventory status of this product call 651-236-5858.

This product may contain chemical substances that are regulated for export by various government agencies (such as the Environmental Protection Agency, the Bureau of Industry and Security, or the Drug Enforcement

Print Date: 01-09-2017

FOSTER 40-50 (FD4050)  
820379PM

## SAFETY DATA SHEET

Administration, among others). Before exporting this product from the USA or Canada, we recommend you contact us at [reg.request@hbfuller.com](mailto:reg.request@hbfuller.com) to request an export review.

This product contains a chemical substance that is subject to a Significant New Use Rule (SNUR) under Section 5(a)(2) of TSCA:

.alpha.-(4-Nonylphenyl)-.omega.-hydroxy-poly(oxy-1,2-ethanediyl)

79 FR 59186, Oct 1, 2014 (Proposed rule)

### FEDERAL REPORTING

#### EPA SARA Title III Section 313

Unless listed below, this product does not contain toxic chemical(s) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR part 372. EPA has advised that when a percentage range is listed the midpoint may be used to fulfill reporting obligations.

Chemical Name	CAS#	%
Barium compounds	13701-59-2	5 - 10
Zinc compounds	1314-13-2	1 - 5
3-Iodo-2-propynyl butylcarbamate	55406-53-6	0.1 - 1

### STATE REPORTING

Proposition 65, The Safe Drinking Water and Toxic Enforcement Act of 1986:

Unless listed below, this product does not contain known levels of any chemical known to the State of California to cause cancer or reproductive harm.

Chemical Name/List	CAS	Percent
Titanium dioxide (Carcinogen)	13463-67-7	1 - 5
Formaldehyde (Carcinogen)	50-00-0	0.001 - 0.01
Acetaldehyde (Carcinogen)	75-07-0	< 10 ppm
Arsenic compounds (inorganic) (Carcinogen)	7440-38-2	< 10 ppm
Lead compounds (Carcinogen)		< 10 ppm

### Substances of Very High Concern (SVHC) Content:

Unless listed below, this product does not contain SVHC's.

4-Nonylphenol, ethoxylated

4-Nonylphenol, ethoxylated

### SECTION 16: OTHER INFORMATION

SDS VERSION DATE: 05-01-2015

This Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS).

HMIS RATING: HEALTH -- 0 FLAMMABILITY -- 0 REACTIVITY -- 0

See SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for personal protective equipment recommendations.

Prepared by: The Global Regulatory Department

Phone: 651-236-5842

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to H.B.Fuller Construction Products, Inc. from its suppliers, and because H.B.Fuller Construction Products, Inc. has no control over the conditions of handling and use, H.B.Fuller



Print Date: 01-09-2017

FOSTER 40-50 (FD4050)  
820379PM**SAFETY DATA SHEET**

---

Construction Products, Inc. makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and H.B.Fuller Construction Products, Inc. assumes no responsibility for use or reliance thereon. It is the responsibility of the user of H.B.Fuller Construction Products, Inc. products to comply with all applicable federal, state and local laws and regulations.