



**Improved  
Performance.  
Absolute  
Confidence.**

**Compliance has never been so easy or economical !**

Introducing the all new, fully functional Protecta PRO™ harnesses and lanyards. With designs that incorporates improved fit, updated colors, and durable yet lightweight construction, Protecta PRO™ gear provides greater comfort and added safety — which translates to reduced worker fatigue and increased productivity. Plus, each and every Protecta PRO™ lanyard now features 3,600 lb. gated hooks meeting ANSI Z359 (USA only)! Go with the gear with exceptional performance and value. Go with Protecta PRO™.

<p><b>1191201</b> STANDARD HARNESS</p> <p><b>1191237</b> STANDARD HARNESS</p>	<p><b>1191205</b> POSITIONING HARNESS</p>	<p><b>1191216</b> RETRIEVAL HARNESS</p>	<p><b>1191224</b> CLIMBING HARNESS</p>	<p><b>1191253</b> STANDARD HARNESS</p>	<p><b>1191270</b> CONSTRUCTION HARNESS</p>	<p><b>1191257</b> RETRIEVAL HARNESS</p>	
<p><b>Back D-Ring; Pass Thru Buckle Legs (1191201C in Canada)</b></p>	<p><b>Back D-Ring; Tongue Buckle Legs (1191237C in Canada)</b></p>	<p><b>Back &amp; Side D-Rings; Pass Thru Buckle Legs (1191205C in Canada)</b></p>	<p><b>Back &amp; Shoulder D-Rings; Pass Thru Buckle Legs (1191206C in Canada)</b></p>	<p><b>Back &amp; Front D-Rings; Pass Thru Buckle Legs (1191224C in Canada)</b></p>	<p><b>Back D-Ring; Quick-Connect Buckle Legs; Back, Shoulder &amp; Leg Padding (1191253C in Canada)</b></p>	<p><b>Back &amp; Side D-Rings; Hip Pad &amp; Belt; Tongue Buckle Legs; Back, Shoulder &amp; Leg Padding (1191270C in Canada)</b></p>	<p><b>Back &amp; Shoulder D-Rings; Quick-Connect Buckle Legs; Back, Shoulder &amp; Leg Padding (1191257C in Canada)</b></p>

**1191209**  
CONSTRUCTION HARNESS  
**Back & Side D-Rings; Hip Pad & Belt; Tongue Buckle Legs (1191209C in Canada)**

**420 lb. (190kg) Capacity**  
**Improved Fit & Performance**  
**Built-In Impact Indicator**  
**Lightweight Hardware**  
**Label Cover**



**PRO™ Shock Absorbing Lanyards** All PRO™ Shock Absorbing lanyards feature durable 1" polyester webbing, 3,600 lb. gated hooks (USA only) and an energy absorbing design that limits fall arrest forces to 900 lbs. or less.



<p><b>1341001</b> 1" web, self locking snap hooks, 6 ft. (1.8m) in length (1341001C in Canada)</p>	<p><b>1341050</b> 1" web, adjustable, self locking snap hooks, 6 ft. (1.8m) in length (1341050C in Canada)</p>	<p><b>1342001</b> 1" web, twin-leg 100% tie-off, self locking snap hooks, 6 ft. (1.8m) in length (1342001C in Canada)</p>	<p><b>1342250</b> 1" web, adjustable twin-leg 100% tie-off, self locking snap hooks, 6 ft. (1.8m) in length (1342250C in Canada)</p>	<p><b>1340125</b> 1" web, self locking snap hook and rebar hook, 6 ft. (1.8m) in length (1340125C in Canada)</p>	<p><b>1340180</b> 1" web, twin-leg 100% tie-off, self locking snap hook and rebar hooks, 6 ft. (1.8m) in length (1340180C in Canada)</p>
<p><b>1340401</b> Cable, self locking snap hooks, 6 ft. (1.8m) in length (1340401C in Canada)</p>	<p><b>1340451</b> Cable, twin-leg 100% tie-off, self locking snap hooks, 6 ft. (1.8m) in length (1340451C in Canada)</p>	<p><b>1340701</b> Rope, self locking snap hooks, 6 ft. (1.8m) in length (1340701C in Canada)</p>	<p><b>1340751</b> Rope, twin-leg 100% tie-off, self locking snap hooks, 6 ft. (1.8m) in length (1340751C in Canada)</p>	<p><b>1340200</b> 1" web, tie-back, self locking snap hooks, 6 ft. (1.8m) in length (1340200C in Canada)</p>	<p><b>1342200</b> 1" web, tie-back, twin-leg 100% tie-off, self locking snap hooks, 6 ft. (1.8m) in length (1342200C in Canada)</p>

**3,600 lb. Gated Hooks (USA only)**  
**Durable Construction**  
**Lightweight Designs**  
**Limits Fall Arrest Forces to 900 lbs. or less**

<p><b>1340040</b> 1" web, tie-back, self locking snap hook and 5K carabiner, 6 ft. (1.8m) in length (1340040C in Canada)</p>	<p><b>1340060</b> 1" web, tie-back, twin-leg 100% tie-off, self locking snap hook and 5K carabiner, 6 ft. (1.8m) in length (1340060C in Canada)</p>	<p><b>1341101</b> Tubular, stretch, self locking snap hooks, 6 ft. (1.8m) in length (1341101C in Canada)</p>	<p><b>1342101</b> Tubular, stretch, twin-leg 100% tie-off, self locking snap hooks, 6 ft. (1.8m) in length (1342101C in Canada)</p>	<p><b>1342125</b> Tubular, stretch, twin-leg 100% tie-off, self locking snap hook and rebar hooks, 6 ft. (1.8m) in length (1342125C in Canada)</p>
--	---	--	---	--

# PRO-STOP™ & PRO™ Stretch Lanyards

## PRO-STOP™ Shock Absorbing Lanyards

PROSTOP™ lanyards feature polyester tubular web opposed to a traditional shock pack, 3,600 lb. gated hooks and an energy absorbing design that limits fall arrest forces to 900 lbs. or less.



**1340220**

*Tubular web, self locking snap hooks, 6 ft. (1.8m) in length (1340220C in Canada)*



**1340230**

*Tubular web, self locking snap hook and rebar hook, 6 ft. (1.8m) in length (1340230C in Canada)*



**1340240**

*Tubular web, twin-leg 100% tie-off, self locking snap hooks, 6 ft. (1.8m) in length (1340240C in Canada)*



**1340250**

*Tubular web, twin-leg 100% tie-off, self locking snap hook and rebar hooks, 6 ft. (1.8m) in length (1340250C in Canada)*



**1340101**

*Tubular stretch web, self locking snap hooks, 6 ft. (1.8m) in length (Not Available in Canada)*



**1340121**

*Tubular stretch web, self locking snap hook and rebar hook, 6 ft. (1.8m) (Not Available in Canada)*

## PRO™ Stretch Shock Absorbing Lanyards

PRO™ Stretch lanyards feature polyester tubular web that expands to 6 ft. (1.8m) and contracts to 4.5 ft. (1.4m), 3,600 lb. gated hooks and an energy absorbing design that limits fall arrest forces to 900 lbs. or less.



**1340141**

*Tubular stretch web, twin-leg 100% tie-off, self locking snap hooks, 6 ft. (1.8m) in length (Not Available in Canada)*



**1340161**

*Tubular stretch web, twin-leg 100% tie-off, self locking snap hook and rebar hooks, 6 ft. (1.8m) (Not Available in Canada)*

# PRO™ Positioning Lanyards & Accessories

## PRO™ Positioning Lanyards

All PRO™ positioning lanyards feature 3,600 lb. gated hooks and are used to maintain a working position - they must not be used for fall arrest applications.



**1385101**

1" web, self locking snap hooks,  
6 ft. (1.8m) in length  
(1385101C in Canada)



**1385301**

1" adjustable web, self locking  
snap hooks, 6 ft. (1.8m)  
(1385301C in Canada)



**1385501**

Rope, self locking snap hooks,  
6 ft. (1.8m) in length  
(1385501C in Canada)



**1351050**

Web rebar assembly, self locking  
snap hooks and rebar hook  
(1351050C in Canada)



**1351001**

Swiveling web rebar assembly,  
self locking snap hooks and rebar  
hook (1351001C in Canada)



**1350200**

Chain rebar assembly, self locking  
snap hooks and rebar hook  
(1350200C in Canada)



**1350150**

Swiveling chain rebar assembly,  
self locking snap hooks, rebar  
hook (1350150C in Canada)

## PRO™ Harness Specifications:

**Max. Arresting Force:** 1,800 lbs. (8 kN)  
**Min. Breaking Strength:** 5,000 lbs. (22.2 kN)  
**Capacity:** 420 lbs. (190 kg) – one user  
**Size:** Small, Medium/Large, X-Large, XX-Large  
**Operating Temperature:** -31°F (-35°C) to 135°F (54°C)  
**Hardware:** Alloy steel  
**Finish:** Zinc plating with clear chromate  
**Webbing:** Polyester 1 3/4" (45 mm)  
**Tensile:** 6,000 lbs. (26.7 kN)  
**Labels:** Vinyl  
**Padding:** Nylon  
**D-Ring Pad:** Polyethylene  
**Standards:** CSA Z259.10-07, OSHA and ANSI Z359.1, A10.32

## PRO™ Lanyard Specifications:

**Max. Arresting Force:** 900 lbs. (4 kN) **Min. Breaking Strength:** 5,000 lbs. (22.2 kN)  
**Capacity:** 310 lbs. (140 kg) – one user  
**Operating Temperature:** -31°F (-35°C) to 135°F (54°C)  
**Hardware:** Alloy steel  
**Finish:** Zinc plating with clear chromate  
**Webbing:** Standard; 1" (25mm) Polyester, 7,500 lb. (30 kN) tensile strength, PRO-Stop™; 1-3/8" (34.4mm) Polyester, 6,600 lbs. (26.4 kN) tensile strength, PRO-Stretch™; 1-15/16" (48.4mm) Polyester, 6,600 lbs. (26.4 kN) tensile strength  
**Rope:** 1/2" Nylon  
**Cable:** 1/4" Vinyl Covered Cable  
**Chain:** Twist 5/0 Zinc Plated  
**Labels:** Vinyl or Avery  
**Thread:** Polyester  
**Standards:** CSA Z259.10-07, OSHA and ANSI Z359.1, A10.32

## PRO™ Accessories

PRO™ accessories offer added flexibility.



**1340260**

Shock absorber with D-ring at one  
end, self locking snap hook at other  
(1340260C in Canada)



**1385000**

D-ring extension with D-ring at one  
end, self locking snap hook at other  
(1385000C in Canada)



### Capital Safety

USA: 800.328.6146 • Canada: 800.387.7484 • Latin America: +1 651.385.4301 • Asia: +65 6558 7758 • Australia: 1800 245 002 New Zealand: 0800 212 505 • Europe, Middle East, Africa: +33 (0)4 97 10 00 10 • Northern Europe: +44 (0) 1928 571324 • Germany: +49 2634 8052  
[www.capitalsafety.com](http://www.capitalsafety.com) • [info@capitalsafety.com](mailto:info@capitalsafety.com)

©2010, Capital Safety  
Form: 9700125 rev: C