

# AW-70

## Technical Information

### AW-70 Cleaner

#### Product Description:

AW-70 is an acidic grout cleaner designed to be used on granite, ceramic, porcelain, quarry tile, and brick floors. AW-70 works great on hard to clean areas such as rest room, kitchen & other high traffic floors. Not for use on marble, travertine, limestone or concrete.

#### Special Features:

Excellent wetting and detergent properties.  
Low foam  
Removes efflorescence

#### Where and When to Use:

For grout joints on granite, ceramic, porcelain, quarry tile, and brick. Do not use on any calcareous surface such as concrete, marble, limestone or terrazzo.

#### Packaging:

32 oz.  
1 gallon (3.8L)  
30 gallon (113.6L)  
55 gallon (208.2L)

#### Storage:

Storage temperature: 120°F (49°C) maximum

#### Directions for use:

- 1) Remove all topical coatings.
- 2) Dilute 1 to 1 with water, add AW-70 to the water.
- 3) Apply solution to the floor surface and allow to stand for 5 minutes.
- 4) Agitate with a brush. Do not let the floor dry. Rinse with clear water.
- 5) Wet vacuum.
- 6) Neutralize with ProStrip at a ratio of 2 oz. per gallon of water.
- 7) Wet vacuum.
- 8) Rinse with clear water.
- 9) Wet vac and let thoroughly dry.
- 10) Apply KleeSeal.

#### Product Specifications:

Physical State: Liquid  
Odor: None  
Appearance: Water clear  
pH: 1.5  
Solubility in water: Infinite  
Specific gravity: 1.32

#### Precautions Summary:

Eyes: Irritating. May injure eye tissue if not removed promptly.  
Skin: Irritating. May cause damage if not removed promptly. Wear rubber gloves.  
Inhalation: Mists are irritating to eyes and respiratory tract in high concentrations.  
Ingestion: Minimal toxicity. Irritating to mouth, throat, and stomach. May cause gastric tract disorder.  
Flash point: Not flammable

#### Notes

Refer to material data sheet (MSDS) for specific health hazard, first aid, and precautionary information.

VMC TECHNICAL ASSISTANCE CORPORATION

8311 EASTPOINT DRIVE, SUITE 800

DALLAS, TX 75227

TELEPHONE

(214)381-8456

FAX

(214)381-4896

WEB

[www.vmctac.com](http://www.vmctac.com)

AW-70  
TECHNICAL INFORMATION

