

ENHANCER

Technical Information

VMC Enhancer - Color Enhancing Impregnator

Product Description:

VMC Enhancer is an environmentally safe, non-toxic, color enhancing stone impregnator. It will protect and enhance the color of all types of unpolished stone and porous cementitious materials. Enhancer is specifically designed to bring out the color in honed, tumbled, aged, brushed, flamed and bush hammered stone.

Special Features:

Oil resistant
Water Resistant
Mildew Resistant
Non-Flammable
Non-Toxic
Ultraviolet Stabilized
Prevents Efflorescence
Long Lasting Protection
Silicone-Free
Environmentally Safe

Where and When to Use:

Enhancer can be used for walls, floors, statues, parking lots and water fountains.

Packaging:

1 gallon (3.8L)
5 gallon (18.9L)

Storage:

Storage temperature: 120°F (49°C) maximum

Directions for use:

- 1) MIX WELL BEFORE USE
- 2) Using a trigger spray bottle, apply a small amount onto surface and buff until dry with a slow speed (175 RPM) floor machine. Use a variable speed hand machine for walls.
- 3) Repeat application until desired results are achieved.
- 4) Do not over apply. Remove all excess Enhancer from the surface before it dries.

Note:

For floors, work in 5ft. x 5 ft. areas. For countertops, work in 2 ft. x 2 ft. areas. The suggested coverage rate for highly porous material is 150-300 sq. ft. gallon (13.9-278.7 sq. meters/3.8 liters), the rate for less porous material is 500-1000 sq. ft./gallon. (46.5-92.9 sq. meters/3.8 liters)

Product Specifications:

Physical State: Liquid
Odor: Slight characteristic
Appearance: White
pH: 7-8
Solubility in water: Infinite
Specific gravity: 1.07

Precautions Summary:

Eyes: May cause irritation
Skin: May cause irritation
Inhalation: Mists may be irritating to respiratory tract in high concentrations
Ingestion: Minimal toxicity and irritation
Flash point: None

Note: Refer to Material Safety Data Sheet (MSDS) for specific health hazard, first aid, and precautionary info.

VMC TECHNICAL ASSISTANCE CORPORATION

8311 EASTPOINT DRIVE, SUITE 800
DALLAS, TX 75227

TELEPHONE
(214)381-8456

FAX
(214)381-4896
www.vmctac.com

ENHANCER
TECHNICAL INFORMATION