

VITRO-CRETE (LL)

Technical Information

VMC TECHNICAL ASSISTANCE CORPORATION

8311 EASTPOINT DRIVE, SUITE 800
DALLAS, TX 75227

TELEPHONE
(214)381-8456

FAX
(214)381-4896

WEB
www.vmctac.com

Vitro-Crete (LL)

Product Description:

Vitro-Crete (LL) is a lithium treatment that strengthens and revitalizes concrete floors by chemically reacting with the substrate. Vitro-Crete (LL) will enhance the surface while making it more durable and abrasion resistant.

Special Features:

Allows the concrete to breathe.
Hardens surface.
Makes surface more abrasion resistant.
Makes surfaces dustless.
Reduces maintenance costs.

Where and When to Use:

Concrete Floors and Countertops.

Packaging:

1 Gallon, 4 per case
5 Gallon
55 Gallon

Storage:

Storage temperature: 120° maximum
Keep from freezing.

Directions for use:

- 1) Thoroughly clean substrate.
- 2) Remove all surface materials such as curing agents, bond breakers, oils, etc.
- 3) Apply a light coat of Vitro-Crete (LL) using a low-pressure sprayer. Do not over apply.
- 4) Allow to dwell 20 minutes or until dry.
- 5) Let surface dry 1-3 hours before allowing traffic, using curing agents or beginning a polishing process.

Product Specifications:

Physical State:	Liquid
Odor:	None
Appearance:	Clear
pH:	12

Precautions Summary:

Eyes: May cause moderate irritation to the eyes
Skin: Causes slight irritation to the skin.
Ingestion: May cause irritation to the mouth, throat, esophagus and other mucous membranes.

Notes

Refer to material safety data sheet (MSDS) for specific health hazard, first aid, and precautionary information.

VITRO-CRETE (LL)
TECHNICAL INFORMATION

